



SPECIFICATIONS

_				
Features	H270TPH 20'	H270TGNBT 20'	H370TGNBT 24'	H370TGN 30'
GVWR	16100 Lbs	17500 Lbs	26250 Lbs	26250 Lbs
GAWR (Per Axle)	7000 Lbs	7000 Lbs	7000 Lbs	7000 Lbs
Tare Weight (approx.)	4225 Lbs	4674 Lbs	5335 Lbs	6382 Lbs
Main Frame	W10 @ 12" I-Beam A992/A572-50	W10 @ 12" I-Beam A992/A572-50	W10 @ 12" I-Beam A992/A572-50	W10 @ 12" I-Beam A992/A572-50
Structural Tubing Crossmembers	3" x 2" x .125 Tubing on 19.2" Centers	3" x 2" x .125 Tubing on 19.2" Centers	3" x 2" x .125 Tubing on 19.2" Centers	3" x 2" x .125 Tubing on 19.2" Centers
Axles	(2) 7000 lb Electric Braking	(2) 7000 lb Electric Braking	(3) 7000 lb Electric Braking	(3) 7000 lb Electric Braking
Suspension	Torsion	Torsion	Torsion	Torsion
Overall Width	102"	102"	102"	102"
Deck Height	38"	38"	38"	38"
Hitch	Pintle Hitch with Adjustable Ball 2 5/16" Ball Coupler	Gooseneck c/w Adjustable 2 5/16" Coupler	Gooseneck c/w Adjustable 2 5/16" Coupler	Gooseneck c/w Adjustable 2 5/16" Coupler
Tires (Radial)	ST235/80R16 Load Range E	ST235/80R16 Load Range E	ST235/80R16 Load Range E	ST235/80R16 Load Range E
Jack	12000# Dropleg Jack	Double 12000# Dropleg Jacks	Double 12000# Dropleg Jacks	Double 12000# Dropleg Jacks
Deck	#1 Kiln Dried Canadian Spruce	#1 Kiln Dried Canadian Spruce	#1 Kiln Dried Canadian Spruce	#1 Kiln Dried Canadian Spruce
Slide in Ramps	Standard			Standard
Beavertail & Double Pivot Ramps		Standard	Double Pivot Spring Assisted TECH Ramps	

Features	H270TPH 20'	H270TGNBT 20'	H370TGNBT 24'	H370TGN 30'
Lights & Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring	LED c/w Fully Protected Arctic Wiring
Options	Spare Tire, Rim & Carrier	Spare Tire, Rim & Carrier, Gooseneck King Pin	Spare Tire, Rim & Carrier, Gooseneck King Pin	Spare Tire, Rim & Carrier, Gooseneck King Pin

Legend for Model Abbreviations

T - Torsion Suspension

GN - Gooseneck

PH - Pintle Hitch

BT - Beavertail

FEATURES

Beavertail & Double Pivot Ramps

The 5.5' beavertail creates an ideal loading incline combined with the ease of spring assisted ramps.

Steps & Grab Handles

Gooseneck step and grab handles make it easier and safer to get up on to the trailer deck.

Open Cleated Beavertail

The open cleated beavertail eliminates the slippage common on wooden beavertails.

Double Pivot Sprng Assisted TECH Ramps

It is now easier than ever to extend the length of your deck with the double pivot spring assisted TECH ramps.

Dual Drop Foot Jacks

Dual HD drop foot jacks and expanded metal basket are standard on all goosenecks, for increased stability, lift and storage capacity.

Hitches

Models are available with either pintle or gooseneck hitches allowing you to match any tow vehicle requirements.

OPTIONS

Spare Tire, Rim and Carrier

Available on:

H270TGNBT 20', H370TGNBT 24', and H370TGN 30'

ST235/85R16 "G" tire upgrade

Available on:

H270TGNBT 20', H270TGNBT 20', H370TGNBT 24', and H370TGN 30'

Double Pivot Spring assisted TECH Ramps

Available on:

H270TGNBT 20', and H370TGNBT 24'

Gooseneck c/w kingpin coupler

Available on:

H270TGNBT 20', H370TGNBT 24', and H370TGN 30'

